

WS-Patina

WS-Patina is an effective spot color for wrought-iron work on pure acrylate basis. It is suitable for indoor and outdoor use. WS-Patina is used for optical change of e.g. stair railings, garden gates, candlesticks, signs, lanterns, bars, lamps. There is no need for subsequent sealing.

- Thixotropic, solvent containing
- Silk mat
- Temperature resistant up to approx. 80° C
- Indoors and outdoors
- Light and weather resistant
- 0011 patina green – 0012 patina copper – 0013 patina silver
0014 patina gold – 0015 patina purple – 0016 patina gold bronze



Surface pretreatment:	WS-Patina can be used on WS-Plast® Thicklayer M4200 and most commercial art forging applications. We recommend a trial coating.
Application:	Patinate discreetly with a brush, rag or sponge.
Thinner:	WS-Plast® thinner MV 751, if other thinners are used, the guarantee expires.
Drying time:	dust dry: approx. 20 minutes touch-proof: approx. 2 hours completely dry: approx. 1 day
Consumption:	No information, depending on the desired effect
Packaging:	250 ml tin, 11 kg pail
Storage stability:	12 month in cool, dry rooms
Viscosity:	thixotropic, i.e. non dripping application is possible on vertical surfaces.
Information:	For professional use only!

August 2018

The regulations of hazardous goods have to be followed. Hazardous goods regulation: subject to labelling. For handling of the product and its substance-specific data please ask for the safety data sheet.

W+S GmbH

Lackchemie und
Aerosol-Technik
Am Sportplatz 5
63791 Karlstein

Tel.: +49(0)6188/9575-0
Fax: +49(0)6188/9575-30
E-Mail: info@ws-lackchemie.de
Web: www.ws-lackchemie.de

Geschäftsführer: Michael Benedict
Amtsgericht Aschaffenburg HRB 6998
UST.-ID Nr. DE197181899
Steuernummer:204/142/80014

HypoVereinsbank Aschaffenburg AG
BIC: HYVEDEMM407
IBAN: DE72 7952 0070 0302 3176 74



Mitglied im Verband der
deutschen Lack- und
Druckfarbenindustrie e.V.



Mitglied im Verband der
Chemischen Industrie e.V.



Mitglied im Verband der
Industrie Gemeinschaft
Aerosole e.V.